

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Touch 'n Foam® Professional Polyurethane Foam Cleaner
Touch 'n Seal® Poly-Clean



PART NUMBER:

GENERAL USE: Solvent cleaner

PRODUCT DESCRIPTION: Flammable aerosol

MANUFACTURER'S NAME

Convenience Products

DATE PREPARED: March 31, 2007

SUPERSEDES: December 9, 2003

Page 1 of 4

ADDRESS (NUMBER, STREET, P.O. BOX)

866 Horan Drive

TELEPHONE NUMBER FOR INFORMATION

(636) 349-5333

(CITY, STATE AND ZIP CODE)

Fenton, MO 63026-2416

COUNTRY

USA

EMERGENCY TELEPHONE NUMBER

Chemtec (800) 424-9300 Outside USA (703) 527-3887

DISTRIBUTOR'S NAME

Same

ADDRESS (NUMBER, STREET, P.O. BOX)

TELEPHONE NUMBER FOR INFORMATION

(CITY, STATE AND ZIP CODE)

COUNTRY

EMERGENCY TELEPHONE NUMBER

SECTION 2 - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	% (by weight)	CAS #	EINECS #	Hazard Symbol	RISK PHRASES Full Text Section 16
Acetone (a,b)	85	67-64-1	200-662-2	F, Xi	R-11, 36, 66, 67
Propane / Isobutane mixture	15	68476-86-8	270-705-8	F+	R-12

(b) See Section 15

(a) Indicates that the Resource Conservation and Recovery Act (RCRA) has determined the waste for this chemical is listed as hazardous and must be handled according to regulations in 40 CFR 260-281.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Aerosol container, contents under pressure, ingredients are extremely flammable, irritating to skin and eyes, can cause serious or fatal complications if swallowed. Do not store over 130° F (54.4° C), do not puncture, do not incinerate. Inhalation of vapors can cause anesthetic effect leading to death in poorly ventilated areas. Hazard Symbols for this product - F+, Xi. Risk Phrases - R12, 36, 66, 67

POTENTIAL HEALTH EFFECTS

INHALATION: Vapors may cause narcosis with headache, difficulty breathing, lightheadedness, drowsiness, unconsciousness and possibly death. Concentrations for 10 minutes may cause dizziness. Very high concentrations (>10,000 ppm) may cause asphyxiation with rapid respiration, reduced mental alertness and muscle coordination, nausea, vomiting, prostration, unconsciousness, convulsions, coma and death.

SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate irritation or dermatitis.

EYES: Direct contact with concentrated vapor or liquid may cause severe irritation.

INGESTION: Moderately toxic; may cause headache, dizziness, diarrhea and general weakness; large doses may result in red blood cell hemolysis.

CARCINOGENICITY

NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Touch 'n Foam ® Professional Polyurethane Foam Cleaner
 March 31, 2007

Page 2 of 4

SECTION 4 - FIRST AID MEASURES

INHALATION: Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.

SKIN: Wash affected area with soap and water; if irritation persists, seek medical attention.

EYES: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

INGESTION: DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.

SECTION 5 - FIRE FIGHTING MEASURES

GENERAL HAZARDS: Flammable gas. Propane is heavier than air and may travel a considerable distance to an ignition source. Keep away from open flame and other sources of ignition. Rapid flame propagation and flashback possible. Do not allow smoking in storage areas or when handling. Containers may rupture violently from pressure when involved in a fire situation.

EXTINGUISHING MEDIA
 Carbon dioxide, dry chemical.

FIRE FIGHTING PROCEDURES

If possible, stop the flow of gas. Firefighters must wear full facepiece self - contained breathing apparatus in positive pressure mode. Fine water spray can be used to keep fire - exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers can explode due to buildup of pressure when exposed to extreme heat. Contents under pressure. Do not use or store near heat or ignition source.

HAZARDOUS COMBUSTION PRODUCTS

Smoke, fumes or vapors, oxides of carbon.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: CAUTION - EXTREMELY FLAMMABLE - EXTREMELY VOLATILE
 - Evacuate and ventilate area, remove all sources of ignition. Product will dissipate rapidly.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. CAUTION - EXTREMELY FLAMMABLE - keep away from all sources of ignition. "Empty" containers may contain residue which may form explosive vapors. Do not puncture container. Do not attempt to refill container. Maintain well ventilated work areas to minimize exposure when handling this material.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HAZARDOUS COMPONENTS	NIOSH				ACGIH			
	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3
Acetone (a,b)	250	590	--	--	500	1188	750	1782
Propane / Isobutane mixture	800	1800			800	1800		

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: None required while threshold limits are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

PROTECTIVE GLOVES: Utilize appropriate gloves for protection needed from cold, based on exposure.

EYE PROTECTION: Chemical splash goggles. Refer to 29 CFR 1910.133 or European Standard EN166.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyewash station nearby.

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Touch 'n Foam ® Professional Polyurethane Foam Cleaner
 March 31, 2007

Page 3 of 4

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR Compressed clear liquid, characteristic solvent odor	VAPOR PRESSURE 70 psig @ 20° C
pH Not applicable	SPECIFIC GRAVITY (WATER = 1) Not determined
BOILING POINT / BOILING RANGE - 44.5° F (- 42.5° C) (Propane)	SOLUBILITY IN WATER Complete
FLASH POINT - 156° F (- 104.4° C) TCC	VISCOSITY Compressed gas
FLAMMABLE LIMITS LEL: 2.1% UEL: 9.5%	VAPOR DENSITY (AIR = 1) > 1
AUTOIGNITION TEMPERATURE 842° F (450° C)	EVAPORATION RATE (WATER = 1) < 1

SECTION 10 - STABILITY AND REACTIVITY

STABILITY UNSTABLE: STABLE: X	CONDITIONS TO AVOID: Extreme temperatures, open flames, sparks.
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids.	

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes or vapors, and smoke may be produced.

HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X	CONDITIONS TO AVOID: None
---	---------------------------

SECTION 11 - TOXICOLOGICAL INFORMATION

Hazardous Components	CAS # EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Acetone (a,b)	67-64-1 200-662-2	9750 mg / kg Oral - rat	16,000 ppm / 4H Inhalation - rat
Propane / Isobutane mixture	68476-86-8 270-705-8	Not determined	Not determined
#REF!	#REF! #REF!	#REF! #REF!	#REF! #REF!
(b) See Section 15			

SECTION 12 - ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. This product may produce hazardous vapors in a closed disposal container creating a dangerous environment. Refer to 40 CFR 260 - 299 for complete waste disposal regulations. Consult your local, state, or federal agency before disposing of any chemicals. According to the European Waste Catalogue, waste codes are application specific and should be assigned by the user based on the application for which the product is used.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Consumer Commodity	IATA HAZARD CLASS / Packaging Group: See Note below
DOT HAZARD CLASS / Packaging Group: ORM - D / None	IMDG HAZARD CLASS: See Note below
REFERENCE: 49 CFR 173.306	RID / ADR Dangerous Goods Code: See Note below
UN / NA IDENTIFICATION NUMBER: None	UN TDG Class / Packaging Group: See Note below
LABEL: CONSUMER COMMODITY	Hazard Identification Number (HIN): None
HAZARD SYMBOLS: None	

Note: Transportation information provided is for reference only. Client is urged to consult 49 CFR 100 - 177, IMDG, IATA, EU, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Touch 'n Foam ® Professional Polyurethane Foam Cleaner
 March 31, 2007

SECTION 15 - REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act)

All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume or Polymer Exemption has been granted in accordance with 40 CFR 723.50.

SARA TITLE III (USA - Superfund Amendments and Reauthorization Act)

311/312 Hazard Categories
 Sudden release of pressure, fire hazard, immediate health hazard

313 Reportable Ingredients:
 None

CERCLA (USA - Comprehensive Response Compensation and Liability Act)

(a) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture = 5,000 lbs) or greater amounts, according to 40 CFR 302.

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There are no reportable chemicals present known to the state of California to cause cancer or reproductive toxicity.

CPR (Canadian Controlled Products Regulations)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS Classification: A, B1, D2B

IDL (Canadian Ingredient Disclosure List)

Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 2.

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.

EINECS (European Inventory of Existing Commercial Chemical Substances)

Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

WGK Water Quality Index:

VbK Index:

RISK PHRASES:

R12 Extremely flammable.
 R36 Irritating to eyes.
 R66 Repeated exposure may cause skin dryness or cracking.
 R67 Vapours may cause drowsiness and dizziness.

SYMBOL(S) REQUIRED FOR LABEL

Flammable Irritant



SAFETY PHRASES:

S2 Keep out of the reach of children.
 S9 Keep container in a well-ventilated place.
 S16 Keep away from sources of ignition.
 S24/25 Avoid contact with skin and eyes
 S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

SECTION 16 - OTHER INFORMATION

Notes & full R-Phrase text

R11 Highly flammable.
 R12 Extremely flammable.
 R36 Irritating to eyes.
 R66 Repeated exposure may cause skin dryness or cracking.
 R67 Vapours may cause drowsiness and dizziness.

HMIS HAZARD RATINGS

HEALTH	1	* = Chronic Health Hazard	2 = MODERATE
FLAMMABILITY	4	0 = INSIGNIFICANT	3 = HIGH
PHYSICAL HAZARD	0	1 = SLIGHT	4 = EXTREME

PERSONAL PROTECTIVE EQUIPMENT B Safety Glasses, Gloves

REVISION SUMMARY:

This MSDS has been revised in the following sections: Complete format revision

MSDS Prepared by: Comprehensive Data Base, Inc.
 P.O. Box 395
 Intercession City, FL 33848 USA
 (863) 644 - 3298 www.compdatabase.com or www.msds.cc

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.