



PRODUCT DATA



Quick Cure

Polyurethane Foam Sealant



Touch 'n Seal Quick Cure polyurethane foam sealant is the easiest means to seal cracks and gaps around plumbing, ventilation outlets, electrical junctions,* between sole plates and concrete slabs, or anywhere you need a fast, economical air-sealing moisture barrier. The All-Direction Dispensing straw system is ideal for maneuvering tight spots. And the special adapter allows for the can to be partially used, stored and re-started later. Quick-Cure is an excellent filler with exceptional expansion and cure time.

- **High Yield - 12 oz can yields up to 918 linear ft.** (1/4" diameter bead) ASTM C-1536
- **Straw & adapter included - no gun needed**
- **Seals & insulates**
- **Class 1 foam**
- **No CFC's, No HCFC's**

* Seal around (never inside) junction boxes.





Quick Cure

Polyurethane Foam Sealant

TECHNICAL DATA:

- Shelf life: 24 months
- Tack-free time: less than 30 minutes (70°F, 40% RH)
- Cure time: 4 hours (70°F, 40% RH)
- Thermal Resistance: (ASTM C-518) R-Value 4.9 per inch thickness
- Density: 1.75 +/- .25 cubic ft.
- Water Vapor Transmission: 10 perm inches
- Contains fire retardant

YIELD ESTIMATE TABLE		
Size(Volume)	Bead Diameter	Linear Feet
24 oz. can	1/4"	1805
	3/8"	818
12 oz. can	1/4"	918
	3/8"	408

ASTM C-1536



DIRECTIONS

Read all directions and cautions before use.

For additional information, see package label or MSDS.

- **PRODUCT IS FLAMMABLE DURING DISPENSING:** Turn off sources of ignition prior to use.
- **SURFACE PREP:** For best results, apply in temperatures between 60-100°F (16-38°C) into spaces with 40% or greater relative humidity. To improve curing in arid regions, spray a light water mist into the cavity before applying foam. Surface should be free of oil and dirt to promote adhesion. Attach straw to adapter, then connect adapter to valve and shake well (30 seconds).
- **APPLICATION:** Testing on scrap material first, hold can upright and activate trigger until foam begins to dispense. Once started, foam can be dispensed at any angle; however, upside-down dispensing is the most efficient means of delivery. Fill gap 1/3 full, leaving room for expansion. Foam continues to dispense for a few seconds after trigger is released. Do not overfill.
- **STORE UPRIGHT BELOW 90°F (32°C)**
- **FOAM BONDS TO SKIN QUICKLY.** Wear gloves, eye protection and work clothes; use drop cloths.
- **FINISH:** Foam is tack free in 30 minutes and dries in 4 hours. Excess can be trimmed, sanded, caulked or plastered as necessary. Direct sunlight discolors foam if not painted.



UNDERWRITERS LABORATORIES INC.
CLASSIFIED CAULKING AND SEALANTS

Surface Burning Characteristics

Applied To Inorganic Reinforced Cement Board*

Flame Spread 10 Smoke Developed 15

R14175
IL15

*Tested as applied in two 3/4 in. diameter beads, 8 inches on center, covering 8.3% of the exposed test sample area.

CAUTION: Contains Polymeric MDI, Polyurethane Resin & Propane / Isobutane. If burned, dried foam may release hazardous decomposition products. Keep away from heat, sparks, flames and static electricity. Turn off sources of ignition (pilot light, etc.). Ventilate work area with moving, fresh air. Vapors heavier than air may cause flash fire or ignite explosively. Do not puncture, expose to heat or store at temperatures above 120°F (49°C). Dried foam may be combustible if exposed to temperatures in excess of 240°F (116°C) Do not leave in auto. Wear protective gloves, safety glasses, work clothes.

FIRST AID TREATMENT - SKIN CONTACT: DO NOT RINSE WITH WATER (water helps curing). If foam is wet: remove immediately with acetone or polyurethane foam cleaner. After removal, wash with soap and water. If foam has dried: it is very difficult to remove. Do not try to remove with solvents. Cured foam wears off and is not harmful to health. **EYE CONTACT:** Flush with water for 15 minutes and get immediate medical attention. **INHALATION:** Overexposure to vapors may cause dizziness or headache – move to fresh air. Consult physician if needed. **INGESTION:** Call a physician. **KEEP OUT OF REACH OF CHILDREN.**

Product	Item #	Case Pack	Unit UPC Code	Master Carton	Case Weight	Pallet Qty.
Quick Cure	4004521212	12 / 12 oz.	0 75650 00057 1	1 00 75650 00057 8	13.04	108
Quick Cure	4004521224	12 / 24 oz.	0 75650 00058 8	1 00 75650 00058 5	23.36	72



Convenience products

866 Horan Dr., Fenton, MO 63026-2416 USA
1-800-325-6180 • www.touch-n-seal.com

MK-095 (03-06)